



07/21/00

UTILITY PATENT APPLICATION TRANSMITTAL UNDER 37 C.F.R. §1.53(b)

ASSISTANT COMMISSIONER FOR PATENTS

Box PATENT APPLICATION

Washington D.C. 20231

Sir:

Transmitted herewith for filing is the patent application of

INVENTOR OR APPLICATION IDENTIFIER: Jae Kyum KIM, Ho Cheol KWON, Jong A PARK, and Kang Mo CHOI
FOR: STRUCTURE OF DRIVING UNIT IN DRUM TYPE WASHING MACHINE

Enclosed are:

1. ☒ 31 pages of specification, claims, abstract
2. ☒ 10 sheets of FORMAL drawing.
3. ☒ 2 pages of newly executed Declaration & Power of Attorney (original).
4. ☒ Priority Claimed to Korean Appln. No. P1999-45088 & P1999-45089, whose entire disclosure is incorporated herein by reference.
5. ☐ Small Entity Statement.
6. ☒ Information Disclosure Statement, Form PTO-1449 and reference.
10. ☒ Authorization under 37 C.F.R. §1.136(a)(3).
11. ☐ Other:
7. ☒ Assignment Papers for LG Electronics Inc. (cover sheet, assignment & assignment fee).
8. ☒ Certified copy of Korean Patent Application No. P1999-45088, filed October 18, 1999 and P1999-45089, filed October 18, 1999.
9. ☒ Two (2) return postcards.
☒ Stamp & Return with Courier.
☒ Prepaid Postcard-Stamped Filing Date & Returned with Unofficial Serial Number.

CLAIMS AS FILED

For	No. Filed		No. Extra	Rate	Fee
Total Claims	20	- 20	0	X \$18.00	\$0.00
Indep. Claims	4	- 3	1	X \$78.00	\$ 78.00
Multiple Dependent Claims (If applicable)				X \$260.00	\$0.00
BASIC FEE					\$690.00
TOTAL FILING FEE					\$768.00

- ☐ This is a Continuation-in-part (CIP) of prior application No: _____ filed _____. Incorporation By Reference-The entire disclosure of the prior application is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
- ☐ Amend the specification by inserting before the first line the sentence:
--This application is a continuation-in-part of Application Serial No. _____ filed _____.--
- ☒ A check in the amount of \$768.00 (Check # 9041) is attached.
- ☐ Please charge my Deposit Account No. 16-0607 in the amount of \$____. A duplicate copy of this sheet is enclosed.
- ☒ The Commissioner is hereby authorized to charge payment of the following fees associated with this communication or credit any overpayment to Deposit Account No. 16-0607. A duplicate copy is enclosed.
- ☒ Any additional filing fees required under 37 C.F.R. 1.16.
- ☒ The Commissioner is hereby authorized to charge payment of following fees during the pendency of this application or credit any overpayment to Deposit Account No. 16-0607. A duplicate copy of this sheet is enclosed.
- ☒ Any patent application processing fees under 37 C.F.R. 1.17.
- ☒ Any filing fees under 37 C.F.R. 1.16 for presentation of extra claims.

FLESHNER & KIM, LLP

Daniel Y.J. Kim
Registration No. 36,186

Correspondence Address Below:

P.O. Box 221200

Chantilly, VA 20153-1200

(703) 502-9440 DYK/mmc

Date: July 21, 2000

jc715 U.S. PTO
09/624144

07/21/00

STRUCTURE OF DRIVING UNIT IN DRUM TYPE WASHING MACHINE

BACKGROUND OF THE INVENTION

Field of the Invention

5 The present invention relates to a drum type washing machine, and more particularly, to a structure of a driving unit in a drum type washing machine.

Background of the Invention

10 In general, a drum type washing, making washing by using friction between a drum rotated by a motor and laundry in a state detergent, washing water, and the laundry are introduced into the drum, provides effects of beating and rubbing washing, but gives almost no damage to the laundry, and shows no entangling of the laundry. A structure of a related art drum washing machine will be explained with reference to FIG. 1. FIG. 1 illustrates a longitudinal section of a related art drum type washing machine, provided with a tub 2 mounted inside of a cabinet 1, a drum 3 rotatably mounted on a central portion of inside of the tub 2. There is a motor 5a under the tub 2 connected with a pulley 18. There is a drum shaft connected to a rear of the drum 3, to which a drum pulley 19 is coupled. And, the drum pulley 19 on the drum shaft and the motor pulley 18 connected to the motor 5a are connected by a belt 20 for transmission of power. And, there is a door 21 in a front part of the cabinet 1, with a gasket 22 between the door 21 and the tub 2. There is a hanging spring between an inside of an upper portion of the cabinet 1 and an outside of an upper portion of the tub 2, and a friction damper 24 between an inside of a lower portion of the cabinet 1 and a lower side of an outside of the tub 2 for damping vibration of the

tub 2 generated during spinning.

However, the related art washing machine has the following disadvantages since driving power of the motor 5a is transmitted to the drum 3 through the motor pulley 18, and the drum pulley 19, and the belt 20 connecting the motor pulley 18 and the drum pulley 19.

5 First, there is a loss of energy in a course of driving power transmission because the driving power is transmitted from the motor 5a to the drum 3, not directly, but through the belt 20 wound around the motor pulley 18 and the drum pulley 19.

And, the driving power transmission from the motor 5a to the drum 3, not directly, but through many components, such as the belt 20, the motor pulley 18, and the drum pulley 19, causes much noise in the course of power transmission.

10 The lots of components required for transmission of driving power from the motor 5a to the drum 3, such as the motor pulley 18, the drum pulley 19 and the belt 20, require many assembly man-hours. And, the more the number of components required for transmission of driving power from the motor 5a to the drum 3, the more number of spots which require repair, and the more frequent at which repair required.

15 In summary, the indirect driving power transmission from the motor 5a to the drum 3 through the motor pulley, the drum pulley, and the belt requires many repair, has much noise, waste of energy, and results in a deterioration of a washing capability.

Moreover, the tub 2 of stainless steel in general in the related art drum washing machine is expensive, has a poor formability, and is heavy.

SUMMARY OF THE INVENTION

Accordingly, the present invention is directed to a structure of a driving unit in a drum type washing machine that substantially obviates one or more of the problems due to limitations

and disadvantages of the related art.

An object of the present invention is to provide a structure of driving unit in a drum type washing machine, which can reduce noise, repair and waste of energy, and moreover, improve washing capability.

5 Another object of the present invention is to provide a structure of driving unit in a drum type washing machine, which has an improved supporting force.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described, the structure of a driving unit in a drum type washing machine having a tub mounted in a cabinet, a drum mounted in the tub, a shaft fixed to the drum for transmission of driving power from the motor to the drum, and bearings mounted on an outer circumference of the shaft at opposite end portions thereof, includes a metallic bearing housing at a central portion of a rear wall of the tub for supporting the bearings mounted on the outer circumferences of opposite end portions of the shaft.

In other aspect of the present invention, there is provided a structure of driving unit in a drum type washing machine including a tub mounted inside of a cabinet, a bearing housing built in a central portion of a rear wall of the tub for supporting a bearing therein, a shaft connected to a drum mounted inside of the tub for transmission of a driving force from a motor to the drum, bearings mounted on an outer circumference of the shaft at opposite end portions thereof

respectively, a rotor coupled to a rear end of the shaft, a stator provided inward of the rotor fixed to the tub rear wall, a connector provided between the shaft and the rotor for transmission of a rotating force from the rotor to the shaft for rotating the shaft and the rotor together, and a supporter fitted between the rear wall of the tub and the stator for supporting the stator and maintaining a concentricity when the stator is mounted to the tub rear wall.

In another aspect of the present invention, there is provided a structure of driving unit in a drum type washing machine including a tub of plastic mounted inside of a cabinet, a metallic bearing housing inserted and built in a central portion of a rear wall of the tub having steps of “┐” and “└” forms on an inner circumference for supporting bearings therein, a shaft connected to a drum mounted inside of the tub for transmission of a driving power from a motor to the drum, having a front end portion fixed to a spider in the drum rear wall, a brass bushing press fit on a region of the shaft from a portion exposed in rear of the spider to the front bearing for prevention of rusting of the shaft, and steps on an outer circumference thereof for fixing mounting positions of the front bearing and the rear bearing on the shaft, bearings mounted on the outer circumference of the shaft at opposite end portions thereof respectively, a rotor of steel or steel alloy plate coupled to the rear end portion of the shaft, including a bent portion formed along a circumference thereof having a setting surface for supporting magnets fitted to an inside of a front portion of a sidewall extended forward from a periphery of a rear wall, and a hub at a center of the rear wall having a through hole for a fastening member, such as a bolt, for coupling the rotor to the shaft, a plurality of cooling fins formed around the hub in a radial direction each with a length for blowing air toward the stator when the rotor is rotated for cooling down a heat generated at the stator, an embossing between adjacent cooling fins on the rear wall of the rotor for reinforcing the rotor, and a drain hole in each of the embossings, for drain of water, a stator

composing the motor together with the rotor, fixed to the tub rear wall inward of the rotor, a connector of plastic provided between the shaft and the rotor for transmission of a rotating force from the rotor to the shaft for rotating the shaft and the rotor together, and a supporter fitted between the rear wall of the tub and the stator for supporting the stator and maintaining a concentricity when the stator is mounted to the tub rear wall.

In further aspect of the present invention, there is provided a structure of driving unit in a drum type washing machine including a tub mounted inside of a cabinet, a drum mounted inside of the tub, a shaft connected to the drum mounted inside of the tub for transmission of a driving force from a motor to the drum, a front bearing and a rear bearing mounted on an outer circumference of the shaft at opposite end portions thereof respectively, a bearing housing built in a central portion of a rear wall of the tub for supporting the front bearing, a rotor composing the motor together with the rotor, and coupled to the rear end portion of the shaft, a stator fixed to the tub rear wall inward of the rotor to compose the motor together with the rotor, a connector serration coupled to the outer circumference of the shaft in front of the rear bearing and fixed to the rotor, for transmission of a rotating power from the rotor to the shaft, and a bearing bracket fixed to the rear wall of the tub to cover an outside of the rotor and support the rear bearing.

In a still further aspect of the present invention, there is provided a structure of driving unit in a drum type washing machine including a tub of plastic mounted inside of a cabinet, a metallic bearing housing inserted to built in a central portion of a rear wall of the tub having steps on an inner circumference for supporting bearings therein, a shaft connected to a drum mounted inside of the tub for transmission of a driving power from a motor to the drum, having a front end portion fixed to a spider in the drum rear wall, and a brass bushing press fit on a region of the shaft from a portion exposed in rear of the spider to the front bearing for prevention of rusting

of the shaft, bearings mounted on the outer circumference of the shaft at opposite end portions thereof respectively, a rotor of steel or steel alloy plate coupled to the rear end portion of the shaft, including a bent portion formed along a circumference thereof having a setting surface for supporting magnets fitted to an inside of a front portion of a sidewall extended forward from a periphery of a rear wall, and a hub at a center of the rear wall having a through hole for a fastening member, such as a bolt, for coupling the rotor to the shaft, a plurality of cooling fins formed around the hub in a radial direction each with a length for blowing air toward the stator when the rotor is rotated for cooling down a heat generated at the stator, an embossing between adjacent cooling fins on the rear wall of the rotor for reinforcing the rotor, and a drain hole in each of the embossings, for drain of water, a stator composing the motor together with the rotor, fixed to the tub rear wall inward of the rotor, a connector of plastic provided between the shaft and the rotor for transmission of a rotating force from the rotor to the shaft for rotating the shaft and the rotor together, a supporter fitted between the rear wall of the tub and the stator for supporting the stator and maintaining a concentricity when the stator is mounted to the tub rear wall, and a bearing bracket fixed to the rear wall of the tub to cover an outside of the rotor and support the rear bearing.

It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain the principles

of the invention:

In the drawings:

FIG. 1 illustrates a longitudinal section of a related art drum type washing machine;

FIG. 2A illustrates a longitudinal section of a drum type washing machine in accordance

with a first preferred embodiment of the present invention;

FIG. 2B illustrates a detailed enlarged view of "A" part in FIG. 2A;

FIG. 3 illustrates a perspective view with a partial cut away view of the rotor in FIG. 2;

FIG. 4 illustrates an enlarged perspective view of "B" part in FIG. 3;

FIG. 5 illustrates a perspective view of a bottom in FIG. 3;

FIG. 6 illustrates a perspective view of the stator in FIG. 2;

FIG. 7 illustrates a perspective view of the connector in FIG. 2;

FIG. 8 illustrates a perspective view of a bottom in FIG. 7; and,

FIG. 9 illustrates a longitudinal section of a driving unit in a drum type washing machine in accordance with a second preferred embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings. A first preferred embodiment of the present invention will be explained in detail with reference to FIGS. 2A ~ 8.

FIG. 2A illustrates a longitudinal section of a drum type washing machine in accordance with a first preferred embodiment of the present invention, FIG. 2B illustrates a detailed enlarged view of "A" part in FIG. 2A, FIG. 3 illustrates a perspective view with a partial cut away view of the rotor in FIG. 2, FIG. 4 illustrates an enlarged perspective view of "B" part in FIG. 3, FIG. 5 illustrates a perspective view of a bottom in FIG. 3, FIG. 6 illustrates a perspective view of the

stator in FIG. 2, FIG. 7 illustrates a perspective view of the connector in FIG. 2, and FIG. 8 illustrates a perspective view of a bottom in FIG. 7.

The drum type washing machine in accordance with a first preferred embodiment of the present invention includes a tub 2 of plastic mounted inside of the cabinet 1, a drum 3 mounted in the tub 2, a shaft 4 fixed to the drum 3 for transmission of driving power from a motor 5 to the drum 3, bearings 6a and 6b fitted on outer circumference of the shaft 4 at both ends thereof, and bearing housings 7 of metal fitted to support the bearings 6a and 6b at a central portion of a rear wall 200 of the tub 2. The bearing housing 7 of metal is formed as a unit with the tub rear wall 200 by an inserted injection molding in the injection molding of the tub 2 of plastic. The bearing housing 7 is preferably formed of aluminum. The bearing housing 7 has steps 8a and 8b for holding the front bearing 6a and the rear bearing 6b fitted in inner circumferences of the bearing housing 7 for preventing the bearings 6a and 6b from being fallen off. Of the steps 8a and 8b formed on the inner circumferences of the bearing housing 7, the front step 8a has a form of “┘” for supporting a rear end portion of the front bearing 6a fitted to a front end of an outer circumference of the shaft 4, and the rear step 8b has a form of “└” for supporting a front end portion of the rear bearing 6b fitted to a rear end portion of the shaft 4. And, there are positioning steps 400a and 400b on outer circumferences of the shaft 4 disposed inside of the bearing housing 7 which transmits driving power from the motor 5 to the drum 3, for fixing mounting positions of the front bearing 6a and the rear bearing 6b on the shaft 4. A front end of the shaft 4 is coupled to a spider 10 in a rear wall of the drum 3, a region of the shaft 4 from a portion exposed in rear of the spider 10 to the front bearing 6a has a bushing 11 of brass press fit thereon for prevention of rusting, and there is a sealing member 12 on an outer surface of the bushing 11 for preventing ingress of water toward the bearing. There is a rotor 13 of a direct

coupling type motor 5 fixed to a center of a rear end of the shaft 4, and a stator 14 of a crown form, consisting the direct coupling type motor 5 together with the rotor 13, fixed to the rear wall 200 inside of the rotor 13.

Referring to FIGS. 3 ~ 5, the rotor 13 of steel or steel alloy plate includes a bent portion formed along a circumference thereof having a setting surface 130 for supporting magnets 13c fitted to an inside of front of a sidewall 13b extended forward from a periphery of a rear wall 13a, and a hub 132 at a center of the rear wall 13a having a through hole 131 for fastening members 15a, such as bolts, for coupling the rotor 13 to the shaft 4. An overall form of the rotor 13 is preferably formed by press forming. There are a plurality of cooling fins 133 each formed to have a preset length in a radial direction around the hub 132 of the rotor 13 for blowing air toward the stator 14 during rotation of the rotor 13 for cooling heat generated at the stator 14. The cooling fins 133 are formed by lancing, to bend the cooling fins 133 at a right angle to the rear wall toward the opening to leave through holes 134 for ventilation. There is an embossing 135 between adjacent cooling fins 133 with a drain hole 136 therein for draining water. There are fastening holes 137 for fastening a connector 16 to the rotor 13 and positioning holes 138 for positioning an assembly position of the connector 16 around the through hole 131 in the hub 132 of the rotor 13 at fixed intervals, which connector 16 is serration coupled to an outer circumference of a rear end portion of the shaft 4 exposed to rear of the rear bearing 6b. The connector 16 is formed of resin having a vibration mode different from the rotor 13 of steel or steel alloy plate, and also serves as a bushing for the rotor 13. As shown in FIGS. 2B, 7 and 8, the connector 16 has fastening holes 162 to correspond to the fastening holes 137 in the hub 132 of the rotor 13 around a circumferential direction of the a peripheral region and a dowel pin 160 between adjacent fastening holes 162 as a unit with the connector 16 for insertion in the

positioning hole 138 in the rotor 13 for self alignment of the fastening holes 137 and 162 in the rotor 13 and the connector 16, respectively. The connector 16 has a serration in an inside circumference of the hub 163 matched to the serration in the rear end of the shaft 4, and reinforcing ribs 161 on outer circumference of the hub 163 for reinforcing the hub 163. There is a hub 201 on the rear wall 200 of the tub 2 having the bearing housing 7 inserted therein when the tub is injection molded, and fastening bosses 202 on an outer side of the hub 201 along a circumferential direction at fixed intervals for fastening the stator 14 to the rear wall 200 of the tub 2. There is a supporter 17 between the rear wall 200 of the tub 2 and the stator 14, of a form almost identical to an outline of the tub rear wall 200, fixed to the tub rear wall 200 when the stator 14 is assembled for supporting the stator 14 and maintaining concentricity of the stator 14. The supporter 17 has a fore end brought into a close contact with an inside of ribs 203 at one side of the tub rear wall 200, and a rear end brought into a close contact with an outer circumference of a rear end of the bearing housing 7 which is not enclosed by the hub 132, but exposed. In the meantime, as shown in FIGS. 2B and 6, the stator 14 includes a magnetic core 145 of segregated layers of magnetic material, a frame 140 of resin coated on the magnetic core 145, a coil 142 wound around each of winding parts 141 on an outer circumference of the frame 140, and fastening ribs 143 on an inside of the frame 140 for fastening the stator 14 to the tub rear wall 200.

The operation of the driving unit in a drum type washing machine in accordance with a first preferred embodiment of the present invention will be explained. Upon causing rotation of the rotor 13 by making a current to flow to the coils 142 of the stator 14 in a sequence under the control of a motor driving controller(not shown) fitted on a panel, the shaft 4 serration coupled with the connector 16 fixed to the rotor is rotated, together with the drum 3 as the power is

transmitted to the drum 3 through the shaft 4.

In the meantime, the drum type washing machine having the driving unit of the present invention applied thereto serves as follows. The tub 2 of the drum type washing machine of the present invention, formed of a plastic with an excellent heat resistance, is light and has a good formability as the tub 2 is injection molded. Since the bearing housing 7 in the drum type washing machine of the present invention is formed of a metal, such as aluminum and the like, the bearing housing 7 is applicable to a drum type washing machine having a drying cycle as the bearing housing shows no thermal deformation. And, since the metallic bearing housing 7 of the present invention is formed integrated with the tub 2 by inserting the bearing housing 7 in the hub 201 on the tub rear wall 200 before the tub 2 of plastic is injection molded, a separate step for assembling the bearing housing 7 to the tub rear wall 200 can be omitted, which simplifies an assembly process, that reduces assembly man-hours. The “┐” form of the step 8a in a front portion of an inner circumference of the bearing housing 7 and the “└” form of the step 8b in a rear portion of an inner circumference of the bearing housing 7 permit to support a rear end of the front bearing 6a and a fore end of the rear bearing 6b mounted on outer circumference of the shaft 4 at both end portions thereof. That is, the steps 8a and 8b on inner circumferences of the metallic bearing housing 7 on both sides thereof prevent both bearings 6a and 6b from being fallen off the bearing housing 7. The positioning steps 400a and 400b on outer circumferences of the shaft 4 at front and rear portions thereof permit easy positioning of the front bearing 6a and the rear bearing 6b on the shaft 4 in the assembly. The front end portion of the shaft 4 is coupled to the spider 10 in the rear wall, and the brass bushing 11 press fit to the region from the exposed portion outside of the spider 10 of the shaft 4 to the front bearing 6a prevents rusting of the shaft 4. The sealing member 12 outside of the bushing 11 prevents ingress of water toward the

bearing.

In the meantime, the rotor 13 of the direct coupling type motor 5 is mounted on a center of the rear end portion of the shaft 4, with the stator 14 disposed on inner side of the rotor, wherein the bend part having the magnet setting surface 130 is formed along a circumferential direction of the sidewall 13b extended forward from a periphery of the rear wall 13a of the rotor 13, for supporting the magnets 13c when the magnets 13c are fitted to an inside surface of the rotor 13, to fabricate the rotor with easy. The through hole 131 of the hub 132 at a center of the rear wall 13a of the rotor 13 permits the fastening member 15b, such as a bolt or the like, to pass therethrough for fastening the rotor 13 to the shaft 4, and the plurality of cooling fins 133 around the hub 132 of the rotor 13 in a radial direction with a length blow air toward the stator 14 during rotation of the rotor 13 for cooling down a heat generated at the stator 14. The cooling fins 133 are formed by lancing , to direct toward the opening of the rotor 13, and to leave through holes 134 for ventilation. The rotor 13 of steel or steel alloy plate is formed by pressing, which shortens a fabrication time period, that improves a productivity. The embossing 135 between the adjacent cooling fins 133 of the rear wall 13a of the rotor 13 improves an overall strength of the rotor 13, and the drain hole 136 in the embossing 135 drains water.

In the meantime, the fastening holes 137 for fastening the connector and the positioning holes 138 for fixing an assembly position of the connector 16 around the through hole 131 in the hub 132 of the rotor 13 permits an easy assembly of the connector 16 to the rotor, which connector 16 is serration coupled to the outer circumference of the rear end portion of the shaft 4 exposed to rear of the rear bearing 6b. That is, once the dowel pins 160 on the connector 16 are inserted in the positioning holes 138 in the rotor 13, the fastening holes 137 and 162 in the rotor 13 and the connector 16 are matched automatically, and by fastening the fastening members

15c through the fastening holes 137 and 162 in the rotor 13 and the connector 16, the connector 16 and the rotor 13 can be assembled with easy. The connector 16 serves to damp vibration from the rotor 13 to the shaft 4 as the connector 16 injection molded of a resin has a different vibration mode from the rotor 13 of steel or steel alloy plate. The serration 164 in the inner circumference of the hub 163 of the connector 16 is fit to the serration 400 in the rear end portion of the shaft 4, to transmit the rotating force of the rotor 13 to the shaft, directly. The reinforcing ribs 161 on an outer circumference of the hub 163 of the connector 16 reinforce the hub 163.

In the meantime, the fastening bosses 202 along a circumference on an outer side of the hub 201 on the rear wall 200 of the tub 2 at fixed intervals permits to fix the stator 14 to the rear wall 200 of the tub 2 by using the fastening boss 202. The supporter 17 between the rear wall 200 of the tub 2 and the stator 14 having a form almost identical to the outline of the rear wall 200 for being fixed to the rear wall 200 of the tub 2 when the stator 14 is fastened permits the stator 14 being supported and maintained of concentricity. That is, once the supporter 17 is fastened to the fastening bosses 204 on the tub rear wall 200, the fore end of the supporter 17 is brought into close contact with an inside surface of the ribs 203 at one side of the tub rear wall 200 and the rear end of the supporter 17 is brought into close contact with the outer circumference of the rear end portion of the bearing housing 7 at a central portion of the tub rear wall 200, which can not be enclosed, but exposed, by the hub 132, such that the supporter 17 supports the stator 14 as well as maintains a concentricity of the stator 14.

The structure of a driving unit in a drum type washing machine in accordance with a first preferred embodiment of the present invention has the following advantages.

The motor direct coupling structure of the drum type washing machine in accordance with a first preferred embodiment of the present invention permits to reduce repair, and power loss.

The bearing housing of metal in the drum type washing machine in accordance with a first preferred embodiment of the present invention shows no thermal deformation, that allows to apply to a product having a drying function.

The rotor of steel or steel alloy plate formed by pressing in the drum type washing machine in accordance with a first preferred embodiment of the present invention requires a very short fabrication time period, with an improved productivity, because the steel or steel alloy plate pressing has an excellent formability.

And, the magnet setting surface on the rotor of the present invention improves a workability in fitting the magnets, and the drain holes, the cooling fins, and the through holes provided to the rotor can prevent overheating of the motor, improve a reliability of the motor, and prolong a lifetime of the motor.

And, the connector having a vibration mode different from the rotor in the drum type washing machine of the present invention can attenuate the vibration transmitted from the rotor to the shaft, and the supporter can support the stator and maintain a concentricity of the stator.

A driving unit in a drum type washing machine in accordance with a second preferred embodiment of the present invention will be explained with reference to FIGS. 3 ~ 9, in detail. FIG. 9 illustrates a longitudinal section of a driving unit in a drum type washing machine in accordance with a second preferred embodiment of the present invention. The rotor, the stator and the connector in the second preferred embodiment of the present invention are identical to those of the first embodiment, to which the same names and reference symbols are given, and will be explained with reference to FIGS. 3 ~ 8.

The drum type washing machine in accordance with a second preferred embodiment of the present invention includes a tub 2 mounted inside of a cabinet 1, a drum 3 mounted inside

of the tub 2, a shaft 4 connected to the drum mounted inside of the tub 3 for transmission of a driving force from the motor 5 to the drum, a front bearing 6a and a rear bearing 6b mounted on outer circumferences of the shaft 4 at both end portions thereof respectively, a bearing housing 7 built in a central portion of the rear wall 200 of the tub 3 for supporting the front bearing 6a, a rotor 13 coupled to the shaft 4, a stator 14 provided inward of the rotor 13 coupled to the tub rear wall 200, a connector 16 serration coupled to an outer circumference of the shaft 4 in front of the rear bearing 6b and fixed to the rotor 13 for transmission of a rotating force of the rotor 13 to the shaft 4, a supporter 17 fitted between the rear wall 200 of the tub 2 and the stator 14 for supporting the stator and maintaining a concentricity when the stator is mounted to the tub rear wall 200, and a bearing bracket 9 fixed to the tub rear wall 200 for covering outside of the rotor 13 and supporting the front end portion of the rear bearing 6b. The tub 2 is formed of plastic, and has an opened front and a closed rear wall 200 of which thickness is greater than a thickness of a sidewall, and the bearing housing 7 at the central portion of the rear wall 200 of the tub 2 is formed of a metal, wherein the bearing housing 7 is insert injection molded when the plastic tub 2 is injection molded, such that the bearing housing 7 is integrated with the tub rear wall 200. The bearing housing 7 is preferably formed of an aluminum alloy.

In the meantime, there is a step 7a on an inner circumference of the metallic bearing housing 7 for supporting the front bearing 6a to prevent the front bearing 7 from being fallen off the bearing housing 7. The step 7a on the inner circumference of the bearing housing 7 has a form of “J” for having a structure which supports a rear end portion of the front bearing 6a mounted on a front end portion of the shaft 4. The front end portion of the shaft 4 is fixed to a spider 10 in the rear wall 200 of the drum 3, a region of the shaft 4 from a portion exposed in rear of the spider 10 to the front bearing 6a has a bushing 11 of brass press fit thereon for prevention

of rusting, and there is a sealing member 12 on an outer surface of the bushing 11 for preventing ingress of water toward the front bearing 6a. There connector 16 is serration coupled to the rear end portion of the shaft 4 for connection between the rotor 13 of the direct coupling type motor 5 and the shaft 4, the rotor 13 is fixed to the connector 16 with fastening members 15c, and the stator 14, forming the direct coupling type motor together with the rotor 13, is fixed to the rear wall 200 of the tub 2 inward of the rotor 13. As shown in FIGS. 3 ~ 5, the rotor 13 of steel or steel alloy plate includes a bend part having a magnet setting surface 130 formed along a circumferential direction of a sidewall 13b extended forward from a periphery of the rear wall 13a of the rotor 13, for supporting magnets 13c fitted to a front portion of an inside surface of the rotor 13, and a hub 132 having a through hole 131 at a center of the rear wall 13a of the rotor 13 so that a fastening member 15a, such as a bolt or the like, can pass through for coupling the rotor 13 to the shaft 4. An overall form of the rotor 13 is preferably formed by pressing. There are a plurality of cooling fins 133 each formed to have a preset length in a radial direction around the hub 132 of the rotor 13 for blowing air toward the stator 14 during rotation of the rotor 13 for cooling heat generated at the stator 14. The cooling fins 133 are formed by lancing, to bend the cooling fins 133 at a right angle to the rear wall 13a toward the opening to leave through holes 134 for ventilation. There is an embossing 135 between adjacent cooling fins 133 with a drain hole 136 therein for draining water. There are fastening holes 137 for fastening a connector 16 to the rotor 13 and positioning holes 138 for positioning an assembly position of the connector 16 around the through hole 131 in the hub 132 of the rotor 13 at fixed intervals, which connector 16 is serration coupled to an outer circumference of a rear end portion of the shaft 4 exposed in rear of the rear bearing 6b. The connector 16 is formed of resin having a vibration mode different from the rotor 13 of steel or steel alloy plate. As shown in FIGS. 7 ~ 9, the connector

16 has fastening holes 162 to correspond to the fastening holes 137 in the hub 132 of the rotor 13 around a circumferential direction of the a peripheral region and a dowel pin 160 between adjacent fastening holes 162 as a unit with the connector 16 for insertion in the positioning hole 138 in the rotor 13 for self alignment of the fastening holes 137 and 162 in the rotor 13 and the connector 16, respectively. The connector 16 has a serration in an inside circumference of the hub 163 matched to the serration in the rear end of the shaft 4, and reinforcing ribs 161 on outer circumference of the hub 163 for reinforcing the hub 163. There is a hub 201 on the rear wall 200 of the tub 2 having the bearing housing 7 inserted therein when the tub is injection molded, and fastening bosses 202 on an outer side of the hub 201 along a circumferential direction at fixed intervals for fastening the stator 14 to the rear wall 200 of the tub 2. There is a supporter 17 between the rear wall 200 of the tub 2 and the stator 14, of a form almost identical to an outline of the rear wall 200, fixed to the tub 2 rear wall 200 when the stator 14 is assembled for supporting the stator 14 and maintaining concentricity of the stator 14. Once the supporter 17 is fastened to the support fastening bosses 204, a fore end of the supporter 17 is brought into close contact with an inside of ribs 203 at one side of the tub rear wall 200, and a rear end thereof is brought into close contact with an outer circumference of a rear end of the bearing housing 7 which is not enclosed by the hub 132, but exposed, thereby the supporter 17 supporting the stator 14 and maintaining a concentricity of the stator. In the meantime, as shown in FIGS. 3 and 6, the stator 14 includes a ring formed frame 140, a coil 142 wound around each of winding parts 141 on an outer circumference of the frame 140, and fastening ribs 143 on an inside of the frame 140 for fastening the stator 14 to the tub rear wall 200.

In the meantime, referring to FIG. 9, there is an "└" formed step 900b at an inner end portion of the bearing bracket 9 fixed to the tub rear wall 200 to cover an outer side of the rotor

13. And, there is a rear bearing fixing member 15b at an rear end of the shaft 4 for supporting a rear surface of the shaft 4 to prevent the rear bearing from being fallen off the shaft 4.

The operation of the driving unit in a drum type washing machine in accordance with a second preferred embodiment of the present invention will be explained. Upon causing rotation of the rotor 13 by making a current to flow to the coils 142 of the stator 14 in a sequence under the control of a motor driving controller(not shown) fitted on a panel, the shaft 4 serration coupled with the connector 16 fixed to the rotor is rotated, together with the drum 3 as the power is transmitted to the drum 3 through the shaft 4.

In the meantime, the drum type washing machine in accordance with the second preferred embodiment of the present invention driven thus serves as follows. Alike the first embodiment of the present invention, since the tub 1 is formed of a plastic with an excellent heat resistance, the tub 1 is light and has a good formability as the tub 2 is injection molded. Since the bearing housing 7 is formed of a metal, such as an aluminum alloy and the like, the bearing housing 7 is applicable to a drum type washing machine having a drying cycle as the bearing housing shows no thermal deformation. And, since the metallic bearing housing 7 is formed integrated with the tub 2 by inserting the bearing housing 7 in the hub 201 on the tub rear wall 200 before the tub 2 of plastic is injection molded, a separate step for assembling the bearing housing 7 to the tub rear wall 200 can be omitted, which simplifies an assembly process, that reduces assembly man-hours. The step 7a in an inner circumference of a front portion of the bearing housing 7 in the second embodiment of the present invention supports a rear end of the front bearing 6a mounted on an outer circumference of the fore end portion of the shaft 4. That is, the “┐” formed step 7a in a front portion of an inner circumference of the metallic bearing housing 7 of the present invention permits to support the front bearing 6a without being fallen off the bearing

housing 7. And, the "└" formed step 900b in an end portion of an inner circumference of the metallic bearing bracket 9 covering an outer side of the rotor 13 fixed to the tub rear wall 200 permits to support a front end of the rear bearing 6b mounted on the rear end portion of the shaft 4, and the rear bearing fixing member 15b on the rear end surface of the shaft 4 prevents the rear bearing 6b from being fallen off the shaft 4.

In the meantime, in the second preferred embodiment of the present invention, since the front bearing 6a is mounted in the bearing housing 7 having insert injection molded in the tub 1, and the rear bearing 6b is mounted in an inside of a center portion of the bearing bracket 9, a distance between the front and rear bearings 6a and 6b on the shaft 4 becomes greater, between which the rotor is mounted. The greater distance between the front and rear bearings 6a and 6b permits to withstand a load caused by imbalance of laundry in the drum 1 during spinning better, and a supporting force to the rotor 13 is enhanced as the rotor 13 of the motor is mounted between the front and rear bearings 6a and 6b. Alike the first preferred embodiment of the present invention, in the second preferred embodiment of the present invention, the brass bushing 11 press fit to the region from the exposed portion outside of the spider 10 of the shaft 4 to the front bearing 6a prevents rusting of the shaft 4. And, alike, the sealing member 12 outside of the bushing 11 prevents ingress of water toward the bearing.

Alike the first preferred embodiment, as shown in FIGS. 3 to 6, the bend part having the magnet setting surface 130 is formed along a circumferential direction of the sidewall 13b extended forward from a periphery of the rear wall 13a of the rotor 13, for supporting the magnets 13c when the magnets 13c are fitted to an inside surface of the rotor 13, to fabricate the rotor with easy. Alike the first preferred embodiment of the present invention, in the second preferred embodiment of the present invention, the plurality of cooling fins 133 around the hub

132 of the rotor 13 in a radial direction with a length blow air toward the stator 14 during rotation of the rotor 13 for cooling down a heat generated at the stator 14. The cooling fins 133 are formed by lancing , to direct toward the opening of the rotor 13, and to leave through holes 134 for ventilation. Since the rotor 13 is formed of steel or steel alloy plate by pressing, which shortens a fabrication time period significantly, a productivity is improved. The embossing 135 between the adjacent cooling fins 133 of the rear wall 13a of the rotor 13 improves an overall strength of the rotor 13, and the drain hole 136 in the embossing 135 drains water.

In the meantime, the fastening holes 137 for fastening the connector and the positioning holes 138 for fixing an assembly position of the connector 16 around the through hole 131 in the hub 132 of the rotor 13 permits an easy assembly of the connector 16 to the rotor, which connector 16 is serration coupled to the outer circumference of the rear end portion of the shaft 4. That is, once the dowel pins 160 on the connector 16 are inserted in the positioning holes 138 in the rotor 13, the fastening holes 137 and 162 in the rotor 13 and the connector 16 are matched automatically, and by fastening the fastening members 15c through the fastening holes 137 and 162, the connector 16 and the rotor 13 can be assembled with easy. The connector 16 serves to damp vibration from the rotor 13 to the shaft 4 as the connector 16 injection molded of a resin has a different vibration mode from the rotor 13 of steel or steel alloy plate. The serration 164 in the inner circumference of the hub 163 of the connector 16 is fit to the serration 400 in the rear end portion of the shaft 4, to transmit the rotating force of the rotor 13 to the shaft, directly. The reinforcing ribs 161 on an outer circumference of the hub 163 of the connector 16 reinforce the hub 163.

In the meantime, the fastening bosses 202 along a circumference on an outer side of the hub 201 on the rear wall 200 of the tub 2 at fixed intervals permits to fix the stator 14 to the rear

wall 200 of the tub 2 by using the fastening boss 202. The supporter 17 between the rear wall 200 of the tub 2 and the stator 14 having a form almost identical to the outline of the rear wall 200 for being fixed to the rear wall 200 of the tub 2 when the stator 14 is fastened permits the stator 14 being supported and maintained of concentricity. That is, the front end of the supporter 17 is brought into close contact with an inside surface of the ribs 203 at one side of the tub rear wall 200 and the rear end of the supporter 17 is brought into close contact with the outer circumference of the rear end portion of the bearing housing 7 at a central portion of the tub rear wall 200, which can not be enclosed, but exposed, by the hub 132, such that the supporter 17 supports the stator 14 as well as maintains a concentricity of the stator 14.

The structure of a driving unit in a drum type washing machine in accordance with a second preferred embodiment of the present invention has the following advantages.

The motor direct coupling structure of the drum type washing machine of the present invention permits to reduce repair, noise and power loss.

The bearing housing of metal in the drum type washing machine of the present invention shows no thermal deformation, that allows to apply to a product having a drying function.

The rotor of steel or steel alloy plate formed by pressing in the drum type washing machine of the present invention requires a very short fabrication time period, with an improved productivity, because the steel or steel alloy plate pressing has an excellent formability.

And, the magnet setting surface on the rotor of the present invention improves a workability in fitting the magnets, and the drain holes, the cooling fins, and the through holes provided to the rotor can prevent overheating of the motor, improve a reliability of the motor, and prolong a lifetime of the motor.

And, the connector having a vibration mode different from the rotor in the drum type

washing machine of the present invention can attenuate the vibration transmitted from the rotor to the shaft, and the supporter can support the stator and maintain a concentricity of the stator.

Particularly, in the second preferred embodiment of the present invention, the greater distance between the front and rear bearings permits to withstand a load caused by imbalance of laundry in the drum 1 during spinning better, and a supporting capability to the rotor is enhanced as the rotor of the motor is mounted between the front and rear bearings.

Thus, by improving a structure of a driving unit of a drum type washing machine, the present invention can reduce noise, repair and power loss, by improving a washing capability, can improve a product reliability, and, by improving workability in fabrication of components of the driving unit, can improve a productivity.

It will be apparent to those skilled in the art that various modifications and variations can be made in the structure of a driving unit in a drum type washing machine of the present invention without departing from the spirit or scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

What is Claimed is:

1. A structure of a driving unit in a drum type washing machine comprising:

a tub of plastic including an opened front, a closed rear wall, and a side wall extended from a periphery of a rear wall to be cylindrical, and a thickness of the rear wall being thicker than that of the side wall;

a drum mounted rotatably in the tub;

a hollow metal bearing housing integrated in a central portion of the rear wall of the tub;

a shaft passed through the bearing housing, the shaft having one end connected to the drum and the other end connected to a rotor of the motor;

bearings mounted between the shaft and the bearing housing for supporting the shaft;

a stator of a crown form fixed at a central portion of the rear wall of the tub, the stator including a magnetic core having a stack of layers of magnetic material and a winding part having a coil wound thereon for forming a magnetic force; and,

a rotor including a back- yoke for forming a flux, a permanent magnet fixed to the back yoke, and a rear wall integrated with the back yoke.

2. A structure as claimed in claim 1, wherein the metallic bearing housing is mounted at a central portion of the rear wall of the tub of plastic as one unit by insert injection molding.

3. A structure as claimed in claim 1, wherein the metal bearing housing is formed of an alloy of aluminum.

4. A structure as claimed in claim 1, wherein the bearing housing has steps on front and

rear portions of inner circumference thereof for supporting a front bearing and a rear bearing respectively positioned on the inner circumference of the bearing housing for preventing respective bearings from being fallen off the bearing housing.

5 5. A structure as claimed in claim 1, wherein, of the steps, a step formed at a front portion of the inner circumference of the bearing housing has a "┐" form for forming a structure which supports a rear end of the front bearing mounted on a front end portion of the shaft among the bearings mounted on opposite end portions of the outer circumference of the shaft, and, of the steps, a step formed at a rear portion of the inner circumference of the bearing housing has a "└" form for forming a structure which supports a front end of the rear bearing mounted on a rear end portion of the shaft among the bearings mounted on opposite end portions of the outer circumference of the shaft.

10 6. A structure as claimed in claim 1, wherein the shaft has a front end portion fixed to a spider in the rear wall of the drum, and a region from a portion exposed to outside of the spider to the front bearing with a brass bushing press fit thereon for prevention of shaft rusting.

7. A structure as claimed in claim 1, further comprising a supporter inserted between the rear wall of the tub and the stator fixed to the rear wall, for making stable fixing of the stator to the tub despite of vibration of the tub and prolonged use.

20 8. A structure as claimed in claim 1, wherein the rotor is formed of steel or steel alloy plate.

9. A structure as claimed in claim 1, wherein the rotor includes;

a bent portion formed along a circumference thereof having a setting surface for supporting magnets fitted to an inside of a front portion of a sidewall extended forward from a periphery of a rear wall, and

5 a hub at a center of the rear wall having a through hole for fastening members for coupling the rotor to the shaft.

10. A structure as claimed in claim 1, wherein the rotor includes;

10 a plurality of cooling fins integrated with the rear wall thereof each formed in a radial direction thereof by lancing to have a length and be directed toward an opening thereof for blowing air toward the stator for cooling down a heat generated at the stator when the rotor is rotated, and

a plurality of through holes formed by the lancing for ventilation.

11. A structure as claimed in claim 10, wherein the rotor further includes;

15 an embossing between adjacent cooling fins on the rear wall of the rotor for reinforcing the rotor, and

a drain hole in each of the embossings, for drain of water.

12. A structure as claimed in claim 1, wherein the rotor further includes;

a hub at a center of the rear wall having a through hole for fastening members for coupling the rotor to the shaft, and

20 fastening holes and positioning holes both formed around the through hole in the hub of

the rotor at fixed intervals, the fastening holes for fastening a connector serration coupled to an outer circumference of the rear end portion of the shaft exposed to rear of the rear bearing, and the positioning holes for positioning an assembly position of the connector.

13. A structure as claimed in claim 12, wherein the connector further includes;

5 a serration formed in an inner circumference of the connector hub matched to the serration formed in the rear end portion of the shaft, and reinforcing ribs on an outer circumference of the connector hub for reinforcing the hub.

14. A structure as claimed in claim 12, wherein the connector is formed of plastic having a vibration mode different from the rotor.

10 15. A structure as claimed in claim 1, wherein the tub includes;

a hub integrated therewith in the rear wall thereof, the hub having the bearing housing inserted therein, and

fastening bosses on an outer side of the hub along a circumferential direction at fixed intervals for fastening the stator to the rear wall of the tub with fastening members.

15 16. A structure as claimed in claim 1, wherein the magnetic core of the stator has segregated core pieces.

17. A structure of driving unit in a drum type washing machine comprising:

a tub of plastic mounted inside of a cabinet;

a metallic bearing housing inserted and built in a central portion of a rear wall of the tub having steps of “┐” and “└” forms on an inner circumference for supporting bearings therein;

a shaft connected to a drum mounted inside of the tub for transmission of a driving power from a motor to the drum, having a front end portion fixed to a spider in the drum rear wall, a
5 brass bushing press fit on a region of the shaft from a portion exposed in rear of the spider to the front bearing for prevention of rusting of the shaft, and steps on an outer circumference thereof for fixing mounting positions of the front bearing and the rear bearing on the shaft;

bearings mounted on the outer circumference of the shaft at opposite end portions thereof respectively;

10 a rotor of steel or steel alloy plate coupled to the rear end portion of the shaft, including a bent portion formed along a circumference thereof having a setting surface for supporting magnets fitted to an inside of a front portion of a sidewall extended forward from a periphery of a rear wall, and a hub at a center of the rear wall having a through hole for a fastening member, such as a bolt, for coupling the rotor to the shaft, a plurality of cooling fins formed around the
15 hub in a radial direction each with a length for blowing air toward the stator when the rotor is rotated for cooling down a heat generated at the stator, an embossing between adjacent cooling fins on the rear wall of the rotor for reinforcing the rotor, and a drain hole in each of the embossings, for drain of water;

a stator composing the motor together with the rotor, fixed to the tub rear wall inward of
20 the rotor;

a connector of plastic provided between the shaft and the rotor for transmission of a rotating force from the rotor to the shaft for rotating the shaft and the rotor together; and,

a supporter fitted between the rear wall of the tub and the stator for supporting the stator

and maintaining a concentricity when the stator is mounted to the tub rear wall.

18. A structure of driving unit in a drum type washing machine comprising:

a tub mounted inside of a cabinet;

a drum mounted inside of the tub;

5 a shaft connected to the drum mounted inside of the tub for transmission of a driving force from a motor to the drum;

a front bearing and a rear bearing mounted on an outer circumference of the shaft at opposite end portions thereof, respectively;

10 a metallic bearing housing built in a central portion of a rear wall of the tub for supporting the front bearing;

a rotor composing the motor together with the rotor, and coupled to the rear end portion of the shaft;

a stator fixed to the tub rear wall inward of the rotor to compose the motor together with the rotor;

15 a connector serration coupled to the outer circumference of the shaft in front of the rear bearing and fixed to the rotor, for transmission of a rotating power from the rotor to the shaft; and,

a bearing bracket fixed to the rear wall of the tub to cover an outside of the rotor and support the rear bearing.

20 19. A structure as claimed in claim 18, wherein the metallic bearing housing is mounted at a central portion of the rear wall of the tub of plastic as one unit by insert injection molding.

20. A structure of driving unit in a drum type washing machine comprising:

a tub of plastic mounted inside of a cabinet;

a metallic bearing housing inserted to built in a central portion of a rear wall of the tub having steps on an inner circumference for supporting bearings therein;

5 a shaft connected to a drum mounted inside of the tub for transmission of a driving power from a motor to the drum, having a front end portion fixed to a spider in the drum rear wall, and a brass bushing press fit on a region of the shaft from a portion exposed in rear of the spider to the front bearing for prevention of rusting of the shaft;

10 bearings mounted on the outer circumference of the shaft at opposite end portions thereof, respectively;

15 a rotor of steel or steel alloy plate coupled to the rear end portion of the shaft, including a bent portion formed along a circumference thereof having a setting surface for supporting magnets fitted to an inside of a front portion of a sidewall extended forward from a periphery of a rear wall, and a hub at a center of the rear wall having a through hole for a fastening member, such as a bolt, for coupling the rotor to the shaft, a plurality of cooling fins formed around the hub in a radial direction each with a length for blowing air toward the stator when the rotor is rotated for cooling down a heat generated at the stator, an embossing between adjacent cooling fins on the rear wall of the rotor for reinforcing the rotor, and a drain hole in each of the embossings, for drain of water;

20 a stator composing the motor together with the rotor, fixed to the tub rear wall inward of the rotor;

a connector of plastic provided between the shaft and the rotor for transmission of a rotating force from the rotor to the shaft for rotating the shaft and the rotor together;

a supporter fitted between the rear wall of the tub and the stator for supporting the stator and maintaining a concentricity when the stator is mounted to the tub rear wall; and,

a bearing bracket fixed to the rear wall of the tub to cover an outside of the rotor and support the rear bearing.

ABSTRACT

Structure of driving unit in a drum type washing machine including a tub mounted inside of a cabinet, a drum mounted inside of the tub, a shaft connected to the drum mounted inside of the tub for transmission of a driving force from a motor to the drum, a front bearing and a rear bearing mounted on an outer circumference of the shaft at opposite end portions thereof respectively, a bearing housing built in a central portion of a rear wall of the tub for supporting the front bearing, a rotor composing the motor together with the rotor, and coupled to the rear end portion of the shaft, a stator fixed to the tub rear wall inward of the rotor to compose the motor together with the rotor, a connector serration coupled to the outer circumference of the shaft in front of the rear bearing and fixed to the rotor, for transmission of a rotating power from the rotor to the shaft, and a bearing bracket fixed to the rear wall of the tub to cover an outside of the rotor and support the rear bearing, thereby reducing noise, repair and power loss, by improving a structure of a driving unit, improving a product reliability, by improving a washing capability, and improving a productivity by improving workability in fabrication of components of the driving unit.

FIG. 1
RELATED ART




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5




FIG. 7




FIG. 8





FIG. 9



Doker No.: _____

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter claimed and for which a patent is sought on the invention entitled _____

STRUCTURE OF DRIVING UNIT IN DRUM TYPE WASHING MACHINE the specification of which

[X] is attached hereto [I was filed on _____ as Application Serial No. _____ and was amended on _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is known to me to be material to patentability in accordance with Title 37, Code of Federal Regulations, Section 1.56(a).

I hereby claim foreign priority or provisional application benefits under Title 35, United States Code, Section 119 of any foreign application(s) for patent or inventor's certificate, or provisional application(s) listed below and have also identified below any foreign application for patent or inventor's certificate, or provisional application(s) having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s) or U.S. Provisional Application(s):			Priority Claimed	
Number	Country	Day/Month/Year	Yes	No
45088 / 1999	Korea	18 / October / 1999	X	
45089 / 1999	Korea	18 / October / 1999	X	

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, Section 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

Prior U. S. Application(s):

Serial No.	Filing Date	Status: Patented, Pending, Abandoned

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I hereby appoint the following attorney(s) and/or agent(s): Daniel Y.J. Kim, Registration No. 36,186 and Mark L. Fleshner, Registration No. 34,596; Carl R. Wesolowski, Registration No. 40,372; John C. Eisenhart, Registration No. 38,128; Ronc A. Vasquez, Registration No. 36,647, all of

The Law Offices of
FLESHNER & KIM
P. O. Box 221200
Chantilly, Virginia 20153-1200

With full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith, and all future correspondence should be addressed to them.

Full name of sole or first inventor: Jae Kyeon KIM

Inventor's signature: 


Date: 2000.7.7

Residence: Kyongsangnam-do, Korea

Citizenship: Republic of Korea

Post Office Address: Hyundai APT., 309-1004, Nae-dong, Kimhae-shi, Kyongsangnam-do, Korea

Full name of sole or first inventor: Ho Cheol KWON

Inventor's signature: 

Date: 2000.7.7

Residence: Kyongsangnam-do, Korea

Citizenship: Republic of Korea

Post Office Address: Dongsung APT., 105-2201, Sapa-dong, Changwon-shi, Kyongsangnam-do, Korea

Full name of sole or first inventor: Jong A PARK

Inventor's signature: 


Date: 2000.7.7

Residence: Kyongsangnam-do, Korea

Citizenship: Republic of Korea

Post Office Address: Jookong APT., 116-206, Kaumchong-dong, Changwon-shi, Kyongsangnam-do, Korea

Full name of sole or first inventor: Kang Mo CHOI

Inventor's signature: 

Date: 2000.7.7

Residence: Kyongsangnam-do, Korea

Citizenship: Republic of Korea

Post Office Address: Hyundai APT., 106-1301, 253-1, Hoggae-ri, Naeso-up, Hoewon-gu, Masan-shi, Kyongsangnam-do, Korea

Full name of sole or first inventor:

Inventor's signature:

Date:

Residence:

Citizenship:

Post Office Address: